

<https://doi.org/10.48047/AFJBS.6.15.2024.7660-7672>



African Journal of Biological Sciences

Journal homepage: <http://www.afjbs.com>



Research Paper

Open Access

IoT-Based Smart Detection of Diabetes using Machine Learning Algorithms

K.Venkatesan¹, V.Malathi², S.Prabakaran³

¹Professor, EEE Department, P.T.Lee.Chengalvaraya Naicker College of Engineering and Technology, Oovery, Kanchipuram-631502. venkatesanjntu7676@gmail.com,

²Assistant Professor-II, EEE Department, SCSVMV University, Enathur, Kanchipuram-631561. ³A.P, ECE Department, P.T.Lee.Chengalvaraya Naicker College of Engineering and Technology, Oovery, Kanchipuram-631502.

Volume 6, Issue 15, Sep 2024

Received: 15 July 2024

Accepted: 25 Aug 2024

Published: 05 Sep 2024

doi: 10.48047/AFJBS.6.15.2024.7660-7672

ABSTRACT

This paper presents the decision tree computation Diabetes Prediction Algorithm (DPA) for the early measure of diabetes dependent upon the datasets. The datasets are assembled by using Internet of Things (IOT) Diabetes Sensors, contains 15000 records, out of which 11250 records are used for getting ready explanation and 3750 are used for testing reason. The proposed computation DPA yielded a precision of 90.02 %, disposition of 92.60%, and exactness of 89.17% and error speed of 9.98%. Further, the proposed computation is differentiated and existing strategies. By and by thereare different computations open which are not completed definite and DPA has an effect. AI is one of the parts of man-made reasoning that permits the improvement of PC frameworks that can gain from encounters without being the need of programming it for each example. AI is essential need of the present condition to take out human exertion just as pretend higher computerization with fewer mistakes. This paper centers on the survey of Early Diabetes discovery utilizing AI procedures and location of the regularly happened messes with it-principally Diabetic retinopathy and diabetic neuropathy. The informational index utilized in a large portion of the concerned writing is Pima Indian Diabetic Data Set. Early diabetes recognition is critical as it assists with lessening the lethal impacts of the diabetes. Different AI strategies like fake neural organization, head part, choice trees, hereditary calculations, Fuzzy rationale and so on have been talked about and analyzed. This paper initially presents the essential thoughts of diabetes and afterward depicts the different strategies used to distinguish it.

KEYWORDS: Diabetes, Recognition, Investigated, Accuracy, Decision-Trees, Error-Rate, Kaggle, ML, Specificity, IoT, Neuropathy, Computerization.

I. INTRODUCTION

Diabetes is one of the diseases that are spreading like scourges in the entire world. It is seen that each age going from kids, youths, youngsters and advanced age are experiencing it. Supportive of long impact can cause more undesirable impacts as far as disappointment of organs like liver, kidneys, heart, stomach and can prompt demise. It is much of the time related with the Disorders-Retinopathy and Neuropathy. Diabetes is fundamentally of two sorts type 1 and type 2 [12].

Type-1 Diabetes: It is the situation wherein liver doesn't produce insulin by any means. Insulin is a chemical that is needed to assimilate glucose from the blood to use this glucose for working out. Nevertheless, deficit of insulin in the body will increase glucose and it will prompt Type-1 Diabetes. It is for the most part found in children and youngsters. It mainly occurs due to the genetic issues. It is regularly known as adolescent problem. Its usual side effects are continuous pee. Weight reduction, expands thirst, obscures vision, and nerves issues. This can be treated by insulin treatment.

Type-2 Diabetes: It is long haul metabolic uncertainty for the most part happens in the grown-ups over age of 40 years. It is evident by high glucose, insulin opposition and high insulin. The significant reason is stoutness and absence of activity. This awful way of life can make glucose get store in the blood and create diabetes. Nearly 90% of individuals influenced by type-2 diabetes in particular. To treat insulin obstruction metformin is given to assurance this can be dealt.

Diabetic Neuropathy: These are the nerve issues formed in diabetic patients with the succession of time. They frequently happen in foot and hands. The normal indications are torment, deadness, shivering, and loss of feeling close by, foot, arms and so on

Diabetic Retinopathy: It is the diabetic problem that prompts long-lasting eye visual impairment. At first there is no critical manifestation, gradually indications are seen. In the subsequent stage, veins are created at the rear of the eyes that could prompt draining on blasting as they are very coordinated.

Diabetes is an unimaginably customary incessant disease from which basically 8.5 percent of the world individuals bears; 422 million individuals all through the planet need to fight with diabetes. The current structures and instruments for diabetic issue assessment and affirmation depend upon the managed methodologies, which need extra and right preparing tests. The arranging tests ought to be gathered and ensured with the investigate assessments sorts, which derives that the style development ought to be considered. As conveyed, the class precision is generally based at the right preparing tests [1].

By and by, a couple of systems proposed to find covered components inside the dataset that isn't completely broke down. Along these lines, the uncommon classifier wishes full scale instructing tests. Hardly any appraisal utilized semi-oversaw class and un-guided

contemplating system to decrease the issues of the data gathering. This might reduce the issues of managed aging trouble, at any rate the exactness and irregularity trim sidedness issue emerge [2]. The tremendous mission of classifier is it needs to lessen the cycles and over-fitting issues. The tree based completely set of principles may in like way languish by methods over such issues [3]. Patients will be ongoing using an IoT-related glucose noticing contraption with worked in alerts. Reliably, patient glucose falls dangerously low while she rests. The alarm sounds, but she can't hear this is since her low glucose levels have conveyed her absent.

Pervasive recognizing empowered by Wireless Sensor Network (WSN) drives are changing the way wherein human organizations was being passed on. This empowers us to assess, impel and handle thriving markers, utilizing sensors and wearable progressions. The increment of these gadgets makes the Internet of Things (IoT), wherein sensors and actuators mix dependably in agreeable security usual structure, and the data is shared across over stages to foster an ordinary working picture (COP). Forming proposes that patients, comparably as amicable insurance suppliers both, will be benefitted by IoT in notactually distant future gave it is finished appropriately. Several clients of social insurance IoT are adaptable healing applications or wearable gadgets that engage patients to get their thriving information. Offices use IoT to screen the space of remedial contraptions, labor force, and patients [14-15][21-22].

Earlier methodologies like Random Forest with accuracy of 85.55%, Bagging with precision of 85.33%, Decision Tree with precision of 85.09%, Artificial Neural Networks with precision of 84.53%, Boosting with accuracy of 84.09%, Naive Bayes with accuracy of 81.01%, Support Vector Machines with precision of 87.6 are proposed by various makers [4-7].

II. Head Component Analysis

PCA is a measurable model that is utilized to characterize informational collection so that the most extreme co-connection can be found in the informational index. It focuses on development to symmetrical plane so information can be ordered alongside this plane, another plane is opposite on it, that is known for second co-connection among informational collection. It helps in highlight extraction and utilizes Eigen esteems and Eigen vectors to compute the essential part [16]. The advantages of head component analysis are 1. It helps in reducing dimension thereby preserving the randomness among data sets. 2. It helps in reducing noise as maximum variation data set is chosen. The disadvantages of head component are 1. There is difficult to calculate Eigen values and covariance matrix, 2. For diabetes detection alone PCA does not give great performance.

III. Naives Bayes Classifier

It is administered learning method dependent on Bayes' hypothesis. It is group of

calculations; it accepts that worth of one specific element is free (credulous) of another component. It represents the contingent likelihood that it decides the probability of an occasion to occur gave that a portion of the occasions have as of now occurred. It is utilized for diabetes identification just as recognition of diabetic retinopathy. The advantages of Naives Bayes classifier are 1. It helps in reducing noise because values are averaged, 2. Higher value of probability gives more accurate result. Disadvantages of Naives Bayes Classifier are 1. It makes very strong assumption about the shape of the data distribution, 2. While making continuous features to discrete, data is lost.

IoT Diabetic sensors are ideal to assemble the Glucose and various limits of the information and these sensors uses the IoT doorways to accumulate MQTT data from the diverse diabetic sensors with in the center and send this it fogs and store this data as datasets. Our paper presents another decision tree computation names Diabetics Prediction Algorithm (DPA) considering the Machine learning, uses dataset accumulated using IOT Diabetes Sensors. From the beginning, the computation is ready with 75% of the data and further attempted with 25% of the data [8]. In the proposed estimation, division centers are surveyed whenever there is a change of the class mark. To pick the best division point, trademark decision measure information gain is embraced. The show extent of the proposed estimation is evaluated using precision, distinction, exactness and screw up rate. Further, the proposed estimation is differentiated and existing disseminated computations [4-7] [9-11]. Our particular commitments in this paper are recorded beneath:

The model is talented to expect diabetics reliant upon the going with attributes: Pregnancies, Plasma Glucose, Diastolic Blood Pressure, Triceps Thickness, Serum InsulinBMI, Diabetes Pedigree, Age followed by class mark: Diabetes, No Diabetes even more satisfactorily. [17]

A clear evaluation against other assumption decision tree computations is played out that give a sensible relationship with show the reasonability of the new model. The new model is computationally useful and makes it fitting for little contraptions like android environment. The proposed model is assessed with different execution measures like exactness, explicitness, accuracy and blunder rate [18].

IV. Analysis of the Literature Survey

Writing Survey of Diabetes Deduction shows that solitary way to deal with identifies diabetes isn't exceptionally modern methodology for early diabetes allowance. Half breed approach with classifiers like Support vector machine, head part examination alongside Genetic calculations, Artificial neural organization would give better outcomes. As these strategies will give assistance in decreasing commotion from informational index by highlight extricating and afterward applying learning philosophy to identify stowed away examples and give more exact outcomes. Irregular woodland will give preferred outcomes over choice trees. Notwithstanding, best blend is joining of AI with fluffy rationale as it will represent the vulnerabilities moreover. The investigation likewise shows a portion of

the savvy approach additionally for diabetes allowance [21].

V. Diabetics Prediction Algorithm

Strategy for assessing the split focuses and choice tree age are Read the preparation dataset T, Sort T in rising request and pick the underlying, Attribute alongside the related class mark, Evaluate the Division Points, as displayed in condition 1.

At first check for change in the class mark. In the event that there is a change of the class mark, evaluate the Division Point and the midpoint of changed class names is the Division Point [22]. For instance, Let V be the basic record and Vi be the second record then division point will be according to the accompanying:

Division Point = Mid-Point (V, Vi)

At last, if the quantity of characteristics is N, we will get N best division focuses for individual ascribes. As choice tree is a twofold tree, there will be just one root hub and consequently, among the N Information Gain esteems pick one best Information Gain worth to frame the root hub. Presently, consider the most extreme Information Gain esteem characteristic as the root hub and take its split point and gap the tree in parallel organization for example keep the qualities which are lesser to part point at the left 50% of the tree and keep the characteristics which are more critical and reciprocals to the right 50% of the tree, and continue with the association till it closes with a noteworthy class name.

VI. Support Vector Machine (SVM)

This is directed learning strategy that implies informational index is prepared so that it might not set in stone yield. It addresses informational collection as marks of cloud in the space. The point here is to develop a hyper-plane that partitions the informational indexes into different classes. The hyper-plane partitions the informational collection into the classes so information mining and arrangement should be possible adequately [19].

This hyper-plane ought to be at greatest edge from the various classes. In any case, in the event that classifications wherein informational index must be characterized are enormous, complex method is utilized known as part arrangement [20]. The advantages of SVM are 1. SVM is used to classify diabetes data set effectively by assigning data set into various categories with the help of the hyperplane, 2. It removes over fit nature of the samples. The disadvantages of SVM are 1. SVM cannot be used for large data sets, 2. SVM is slow in its execution.

VII. Fuzzy C-means

It is an augmentation of K-means clustering calculation that implies it targets shaping the groups, then, at that point, discovering the centroids of the groups, the approaching informational collection is allotted to that bunch that has least separation from its

centroid [23]. Notwithstanding, it might happen that occasionally extremely less edge is there so new informational collection can be succumbing to more than one group. This was stayed away from by fluffy C-implies bunching calculation as it utilizes fluffysegment that records for the enrolment work. Consequently, results produce are more precise. The advantages of Fuzzy C-means are 1. The involvement of fuzzy logic here that account of the membership function helps in giving better result for the classification, 2. It is unsupervised learning technique so results are more real time. The disadvantages of Fuzzy C-means are 1. It takes long computational time, 2. It is more susceptible to wrong guesses at initial stages.

Table 1 shows the model dataset assembled using IOT Diabetes Sensors. In the table P shows Pregnancies, PG exhibits Plasma Glucose, DBP exhibits Diastolic Blood Pressure, TT exhibits Triceps Thickness, SI shows Serum Insulin, DP shows Diabetes Pedigree. At first Division Points are figured for the information displayed in Table 1. The figured Division Points are displayed in Table 2.

Table 1. Informational index gathered utilizing IOT Diabetes

P	PG	DBP	TT	SI	BMI	DP	Age	Class
0	171	80	34	23	43.5	1.21	21	No Diabetes
8	92	93	47	36	21.2	0.15	23	No Diabetes
7	115	47	52	35	41.5	0.07	23	No Diabetes
9	103	78	25	304	29.5	1.20	43	Diabetes
1	85	59	27	35	42.6	0.54	22	No Diabetes
0	82	92	09	253	19.7	0.10	26	No Diabetes
0	133	47	19	227	21.9	0.17	21	No Diabetes
0	67	87	43	36	18.2	0.23	26	No Diabetes
8	80	95	33	24	26.6	0.44	53	Diabetes
1	72	31	40	42	36.8	0.10	26	No Diabetes
1	88	86	11	58	43.2	0.23	22	No Diabetes
3	94	96	31	36	21.2	0.44	23	No Diabetes
5	114	101	43	70	36.4	0.10	38	Diabetes
7	110	82	16	44	36.0	0.28	25	No Diabetes
0	148	58	11	179	39.1	0.16	45	No Diabetes
3	109	77	46	61	19.8	0.20	21	Diabetes
3	106	64	25	51	29.0	0.58	42	Diabetes
1	156	53	15	226	29.7	0.20	41	Diabetes
8	117	39	32	164	21.2	0.08	25	No Diabetes
3	102	100	25	289	42.1	0.17	43	Diabetes

Table 2. Computed Division Points

Attributes	No. of Division Points	Division Points
P	9	0.5, 1.0, 2.0, 3.0, 4.0, 6.0, 7.5, 8.0, 8.5
PG	8	112.0, 81.0, 163.5, 98.0, 114.5, 76.0, 152.0, 109.5
DBP	7	98.0, 61.5, 50.0, 94.0, 55.5, 79.0, 95.5
TT	10	13.0, 22.0, 26.0, 32.5, 44.5, 33.5, 41.5, 15.5, 46.5, 43.0
SI	9	226.5, 271.0, 54.5, 117.0, 202.5, 23.5, 29.5, 47.5, 59.5
BMI	8	24.28, 32.93, 36.29, 36.69, 20.53, 42.39, 41.84, 19.78
DP	9	0.21, 0.17, 0.56, 1.24, 0.90, 0.36, 0.07, 0.08, 0.49
AGE	4	32.0, 44.0, 49.0, 21.0

In light of the Division Points and Information Gain esteems, rules are created as observes and the produced choice tree is displayed in Figure 1.

1: If [(H < 32.0) and (F < 20.539154) and (F < 19.785736)] Then (assumption = NoDiabetes)

2: If [(H < 32.0) and (F < 20.539154) and (F >= 19.785736)] Then (expectation =

Diabetes)3: If [(H < 32.0) and (F >= 20.539154)] Then (expectation = No Diabetes)

4: If [(H >= 32.0) and (D < 13.0)] Then (expectation = No

Diabetes)5: If [(H >= 32.0) and (D >= 13.0)] Then (expectation

=Diabetes) H (7)

| - < 32.0

| F (5)

| - < 20.539154

| F (5)

|| - < 19.785736

|| No Diabetes

|| - >= 19.785736

|| Diabetes

| - >= 20.539154

| No Diabetes

| - >= 32.0

| D (3)

| - < 13.0

| No Diabetes

| - >= 13.0

| Diabetes

VIII. Results and Discussion

For the experimentation, dataset with 15000 records and 8 ascribes are gathered utilizing IOTDiabetes Sensors. At first, the calculation is prepared with 75% of the information and further tried with 25% of the information. In the proposed calculation, division focuses are assessed at whatever point there is an adjustment of the class name. To pick the best division point, property determination measure data gain is embraced. The calculation is coded utilizing Net Beans IDE and executed in intel i3 processor, 4 GB RAM. The exactness of the proposed model Diabetes Prediction Algorithm (DPA), displayed in Table 3, is contrasted and the current methodologies: Random Forest, Bagging, Decision Tree, Artificial Neural Networks, Boosting, credulous Bayes and Support Vector Machines individually. The proposed model yielded an exactness of 90.02 %, better when contrasted and past approaches. The pictorial portrayal of exactness examination is displayed in Figure 2. The mistake pace of the proposed model Diabetes Prediction Algorithm (DPA), displayed in Table 4, is contrasted and the current methodologies: Random Forest, Bagging, Decision Tree, Artificial Neural Networks, Boosting, credulous Bayes and Support Vector Machines individually. The proposed model yielded an exactness of 9.98 %, better when contrasted and past approaches. The pictorial portrayal of exactness examination is displayed in Figure-3

Table 3. Accuracy examination with existing methodologies

Model name	Error Rate (%)
(RF)	14.442
Bagging	14.667
(DT)	14.91
ANN	15.468
Boosting	15.902
(NB)	18.99
SVM	12.4
DPA	6.2




Figure 2. Accuracy comparison with existing approaches

Table 4. Error Rate comparison with existing approaches

Model Name	Error Rate (%)
Random Forest (RF)	14.1
Bagging	14.7
Decision Tree (DT)	15
ANN	15.5
Boosting	16
Naïve Bayes (NB)	19
SVM	12.2
DPA	6.7



Figure 3. Error-Rate comparison

Further, proposed DPA is differentiated and Decision Stump, Hoeffding Tree, Naïve Bayes and Simple Logistic Algorithms using the data accumulated from IOT Diabetes Sensors to the extent accuracy, and the results are shown in Table 5. Here, we used WEKA contraption for finding the precisions of existing estimations.

Table 5. Precision Comparison with different calculations utilizing Weka

Model Name	Accuracy (%)
Choice Stump	78
Hoeffding Tree	87.36
Innocent Bayes	79.36
Straightforward Logistic	79.14
DPA	90.02

Further, proposed DPA is differentiated and Decision Stump, Hefting Tree, Naïve Bayes and Simple Logistic Algorithms using the data assembled from IOT Diabetes Sensors to the extent bungle rate, and the results are shown in Table 6. Here, we used WEKA contraption for finding the bumble speed of existing computations.

Table 6. Error Rate Comparison with different calculations utilizing Weka

Model Name	Error Rate (%)
Choice Stump	22
Hoeffding Tree	12.64
Guileless Bayes	20.64
Straightforward Logistic	20.85
DPA	9.98

Further, proposed DPA is differentiated and Decision Stump, Hoeffding Tree, Naïve Bayes and Simple Logistic Algorithms using the data assembled from IOT Diabetes Sensors to the extent precision, and the results are shown in Table 7. Here, we used WEKA gadget for finding the exactness of existing computations.

Table 7. Precision Comparison with different calculations utilizing Weka

Model Name	Precision (%)
Choice Stump	84.5
Hoeffding Tree	87.2
Gullible Bayes	78.9
Basic Logistic	78.6
DPA	89.12

Further, proposed DPA is differentiated and Decision Stump, Hoeffding Tree, Naïve Bayes and Simple Logistic Algorithms using the data assembled from IOT Diabetes Sensors to the extent distinction, and the results are shown in Table 8. Here, we used WEKA gadget for finding the identity of existing computations.

Table 8.Precision Comparison with other algorithms using Weka

Model Name	Specificity (%)
Decision Stump	78.0
Hoeffding Tree	87.4
Naïve Bayes	79.4
Simple Logistic	79.1
DPA	

IX. Conclusions

In this paper, creators proposed Diabetes Prediction Algorithm (DPA) for the early recognition of diabetes utilizing Internet of Things Diabetes Sensors and gathered 15000 records with 8 credits followed by 2 class marks. For experimentation, 75% of the information is utilized for preparing reason and 25% of the information is utilized for testing reason. DPA calculation is thought about as far as exactness, particularity, accuracy and blunder rate with existing calculations utilizing WEKA instrument. Further, DPA calculation is contrasted and existing distributed calculations. By and large, DPA calculation is beating when contrasted and every one of the methodologies and yielded an exactness of 90.02 %, blunder pace of 9.98%, accuracy of 89.12% The crossover approaches yield preferable outcomes over single classifiers. Also, a portion of the strategies when incorporated with fluffy rationale gives better outcomes. Not just this, Diabetic retinopathy and Diabetic neuropathy can likewise be examined with fluffy rationale incorporated with picture examination.

These strategies can be joined with continuous information with the assistance of "Web of Things" to make ongoing gadgets for the medical care applications. Consequently, IOT with knowledge would be procured. These gadgets will take out need of human contribution at bigger speed and will give teach the better outcomes with less mistakes. Informational index so obtained or constant information contain uproarious information that should be mined from appropriate information revelation. Consequently, classifiers like SVM and PCA ought to be utilized alongside more refined strategies for legitimate component extraction. Fake neural organization represents the downside of shakiness of learning of information hubs, this should be work upon. For Principal part examination, choice of Eigen esteems measures ought to be more work upon. Irregular Forest Classifiers require checking for the time intricacy. Thus, diabetes derivation can be viable with these procedures.

References

1. Akolekar, Ranjit, Argyro Syngelaki, Rita Sarquis, Mona Zvanca, and Kypros H. Nicolaidis. "Prediction of early, intermediate and late pre eclampsia from maternal

- factors, biophysical and biochemical markers at 11-13 weeks." *Prenatal diagnosis* 31, no. 1 (2011): 66-74.
2. Alssema, M., D. Vistisen, M. W. Heymans, G. Nijpels, C. Glümer, P. Z. Zimmet, J. E. Shawet al. "The Evaluation of Screening and Early Detection Strategies for Type 2 Diabetes and Impaired Glucose Tolerance (DETECT-2) update of the Finnish diabetes risk score for prediction of incident type 2 diabetes." *Diabetologia* 54, no. 5 (2011): 1004-1012.
 3. Farran, Bassam, Arshad Mohamed Channanath, Kazem Behbehani, and Thangavel Alphonse Thanaraj. "Predictive models to assess risk of type 2 diabetes, hypertension and comorbidity: machine-learning algorithms and validation using national health data from Kuwait-a cohort study." *BMJ open* 3, no. 5 (2013).
 4. Faust, Oliver, Rajendra Acharya, Eddie Yin-Kwee Ng, Kwan-Hoong Ng, and Jasjit S. Suri. "Algorithms for the automated detection of diabetic retinopathy using digital fundus images: a review." *Journal of medical systems* 36, no. 1 (2012): 145-157
 5. Huang, Guang-Bin, Hongming Zhou, Xiaojian Ding, and Rui Zhang. "Extreme learning machine for regression and multiclass classification." *Systems, Man, and Cybernetics, Part B: Cybernetics, IEEE Transactions on* 42, no. 2 (2012): 513-529
 6. Jensen, Morten Hasselstrøm, Zeinab Mahmoudi, Toke Folke Christensen, Lise Tarnow, Edmund Seto, Mette Dencker Johansen, and Ole Kristian Hejlesen. "Evaluation of an algorithm for retrospective hypoglycemia detection using professional continuous glucose monitoring data." *Journal of diabetes science and technology* 8, no. 1 (2014): 117-122.
 7. Kalaiselvi, C., and G. M. Nasira. "Classification and Prediction of Heart Disease from Diabetes Patients using Hybrid Particle Swarm Optimization and Library Support Vector Machine Algorithm."
 8. Karthikeyan, T., and K. Vembandasamy. "A Novel Algorithm to Diagnosis Type II Diabetes Mellitus Based on Association Rule Mining Using MPSO- LSSVM with Outlier Detection Method." *Indian Journal of Science and Technology* 8, no. S8 (2015): 310- 320.
 9. Karthikeyan, T., and K. Vembandasamy. "A Refined Continuous Ant Colony Optimization Based FP- Growth Association Rule Technique on Type 2 Diabetes." *International Review on Computers and Software (IRECOS)* 9, no. 8 (2014): 1476-1483.
 10. Kuo, R. J., S. Y. Lin, and C. W. Shih. "Mining association rules through integration of clustering analysis and ant colony system for health insurance database in Taiwan." *Expert Systems with Applications* 33, no. 3 (2007): 794-808.
 11. Nahar, Jesmin, Tasadduq Imam, Kevin S. Tickle, and Yi-Ping Phoebe Chen. "Association rule mining to detect factors which contribute to heart disease in males and females." *Expert Systems with Applications* 40, no. 4 (2013): 1086-1093.

12. Allugunti, V.R., Kishor Kumar Reddy, C., Elango, N.M., Anisha, P.R. (2021). Prediction of Diabetes Using Internet of Things (IoT) and Decision Trees: SLDPs. In: Satapathy, S., Zhang, Y.D., Bhateja, V., Majhi, R. (eds) *Intelligent Data Engineering and Analytics. Advances in Intelligent Systems and Computing*, vol 1177. Springer, Singapore. https://doi.org/10.1007/978-981-15-5679-1_43
13. Dang, N., Khanna, A., Allugunti, V.R. (2021). TS-GAN with Policy Gradient for Text Summarization. In: Khanna, A., Gupta, D., Pólkowski, Z., Bhattacharyya, S., Castillo, *Data Analytics and Management. Lecture Notes on Data Engineering and Communications Technologies*, vol 54. Springer, Singapore. https://doi.org/10.1007/978-981-15-8335-3_64.
14. V. Reddy Allugunti and N. Elango, "Development of a Generic Secure Framework for Universal Device Interactions in IoT of Fifth Generation Networks," 2018 Second World Conference on Smart Trends in Systems, Security and Sustainability (WorldS4), 2018, pp. 238-245, doi: 10.1109/WorldS4.2018.8611592.
15. Prof. D. Jayaramaiah, A.Prasanth, A.Viswanatha Reddy, Dr.Anirban Basu, 2012, Multi Agent Management System for Next Generation Mobile Networks. [MAMS for NGMN], *International Journal of Engineering Research & Technology (IJERT)* Volume 01, Issue 07 (September 2012)
16. Prof. D. Jayaramaiah, A. Viswanatha Reddy, Srikishan. D. Agent based User Interface Design for Mobile Cloud Computing Environment (AUID) , *International Journal of Engineering Innovations and Research(IJEIR)* Volume 1 Issue 3, May 2012.
17. Prof. D. Jayaramaiah, A.Prasanth, A.Viswanatha Reddy, Dr.Anirban Basu, 2012, Multi Agent Management System for Next Generation Mobile Networks. [MAMS for NGMN], *International Journal of Engineering Research & Technology (IJERT)* Volume 01, Issue 07 (September 2012).
18. Reddy, V., Allugunti, , M, E. & Reddy, C. K. (2019). Internet of things based early detection of diabetes using machine learning algorithms: Dpa. *International Journal of Innovative Technology and Exploring Engineering*, 8(10):1443-1447. doi: 10.35940/ijitee.A1013.0881019.
19. Basu, Anirban. "Agent Based QoS Provisioning for NGMN (LTE)." (2013).
20. V. Reddy Allugunti and N. Elango, "Development of a Generic Secure Framework for Universal Device Interactions in IoT of Fifth Generation Networks," 2018 Second World Conference on Smart Trends in Systems, Security and Sustainability (WorldS4), 2018, pp.238-245, doi: 10.1109/WorldS4.2018.8611592.
21. Allugunti, V., M, E. & Reddy, C. K. (2019). Diabetes kaggle dataset adequacy scrutiny using factor exploration and correlation. *International Journal of Recent Technology and Engineering*, 8(1 Special Issue4):1105-1110.