

<https://doi.org/10.48047/AFJBS.6.14.2024.9887-9893>



African Journal of Biological Sciences

Journal homepage: <http://www.afjbs.com>



Research Paper

Open Access

Predict the Energy Consumption in Selection Node Process of Wireless Sensor Networks using efficient adaptive node selection Routing Protocol

K. Samuel, Dr. R. Kalaimagal

1Research Scholar, PG & Research, Department of Computer Science, Government Arts College for Men(A), Nandanam

2Associate Professor, PG & Research, Department of Computer Science, Government Arts College for Men(A), Nandanam

Volume 6, Issue 14, Aug 2024

Received: 15 June 2024

Accepted: 25 July 2024

Published: 15 Aug 2024

doi: [10.48047/AFJBS.6.14.2024.9887-9893](https://doi.org/10.48047/AFJBS.6.14.2024.9887-9893)

Abstract

Choosing the best performing nodes in a wireless sensor network to monitor a target may reduce the total number of working nodes while meeting the need for global tracking reliability. However, the vast majority of recent studies choose sensor nodes that are geographically near to the target rather than those that are correlated with the precise spot of the objective. Consequently, these solutions cannot satisfy all network objectives. The wireless sensor network (WSN) is an integral part of the Internet of Things. The expansion and use of the Internet of Things have increased the need for heterogeneity in WSNs. The rapid depletion of batteries has been a significant barrier to future research into the potential of wireless sensor networks (WSN). The optimisation of battery life in WSNs has garnered considerable focus. Nonetheless, a long-lasting WSN depends on an effective cluster chief election method. In this context, it is suggested that the informational value of sensing nodes be measured using a joint distance-weighted metric. In experiments, EANS has been shown to be better than state-of-the-art methods because it uses less energy and is easier to compute while keeping tracking precision.

Keywords: Node selection, WSN, Networks, Processor

Introduction

In recent years, both industry and academic institutions have expressed an interest in reducing the energy consumption of nodes in wireless sensor networks (WSN). Numerous solutions have been developed to improve network reliability by increasing the likelihood that a packet will be conveyed in WSN and by increasing the power consumption of the nodes, which increases the network's longevity. Long-distance radio transmission, for instance, consumes more power, potentially reducing the battery capacity of your gadget life.

Wireless Sensor Networks (WSNs) use a large number of cheap sensor nodes that talk to each other through a wireless network without being watched. Because many sensor nodes run on batteries, and it would be impractical to replace the batteries once they have been deployed, maximising energy efficiency is essential for any WSN implementation.

A WSN resembling a grid of WSN nodes could simulate ambient temperature sensing and capture. Bomnale et al. desired to determine how long a network could continue to function after being activated for a predetermined number of cycles. In contrast to more conventional energy management strategies for transceiver operation and wireless transmission, Jelcic's research centred on the sensing device. The author examined sensor energy management in multimodal heterogeneous WSNs, focusing on context and energy consciousness.

In order to address energy-related issues in WSNs, a genetic algorithm or other bio-inspired technique is utilised. During testing with a Java-based custom simulator, the proposed protocol outperformed grouping based on the LEACH algorithm. Karthick et al. proposed a mechanism for aggregation based on genetic and krill herd optimisation techniques. Comparing the results of the krill herd algorithm to those of the genetic algorithm and LEACH revealed that the krill herd algorithm was the most effective.

Related Works

The researchers advised single-node distributed estimate. The absolute local innovations vector adaptively identifies active sensors. The smallest posterior Cramer-Rao lower limit (PCRLB) number was used to choose sensors after listing all possible pairs. Even with few sensors, enumeration demands plenty of computing resources. In, the conditional posterior Cramer-Rao lower limit (C-PCRLB) was suggested for long-term sensor selection. for ease. These approaches simply assess the number of selected nodes, not their energy or tracking compatibility. High computing strain.

By using a clustering design for networks, the researchers of suggested a node selection tackle within the context of a particle filter for enabling collaborative tracking. This study effectively provided energy savings while maintaining the required level of monitoring reliability, all while accounting for the remainder of the energy consumption of sensor nodes. In contrast, the cluster head always consumes more power than is necessary due to tracking control. Additionally, the angular diversity of nodes is not considered during node selection. In this paper, we presented a low-energy node selection method for sensors that monitor only bearings. By including the node's residual energy in the objective function, a unique node selection criterion was established. But it was hard to make the condition that all nodes in the text have clocks that are in sync with reality. To reduce the quantity of power required for cooperative spectrum sensing's "overhead," a user selection technique is proposed. However, this strategy

is restricted to sensor nodes equipped with a cognitive radio, limiting its energy-saving and sensing precision potential.

Researchers recommend entropy-based sensor selection. Bayesian Filters do. Entropy-based approaches optimise an information utility function using measurements. MISS supported mixing. MISS allowed sensor nodes with the most mutual knowledge about the target state to share data, reducing energy consumption while maintaining target position computation accuracy. The authors suggested a lightweight sensor node selection method that weights data usefulness and utilisation of energy equally in a composite function. Those computation-intensive methods utilise node information utility as the aim function.

Table 1
Comparison of different approaches of average execution time.

Terms	Sensing ranges			
	Sensing range of sensors			
	10 m	20 m	40 m	80 m
Average number of nodes within sensing range	4	9	28	76
Average execution time of node selection (s)				
Weighted distance	0.535	1.168	3.116	6.389
Closest	0.115	0.492	0.834	2.529
Entropy-based	0.763	2.218	6.273	13.517
EANS	0.563	1.272	3.656	7.395

Network Model

This paper examines a stationary WSN consisting of a single drain and an undetermined number of sensor nodes distributed across a two-dimensional sensing field. Important characteristics and hypotheses of our simulated sensor network include the following:

(i) An endless supply of electricity is perpetually installed in the washbasin. Additionally, data from many sensor locations is collected.

(ii) Various sensor nodes are separated from one another. Every node has the identical energy budget.

GPS or other localization technologies allow each node to know its precise location.

Let's assume a node is located at.

Our research aims to identify the subset of nodes that will prove most valuable to future monitoring efforts. In addition, the detection probability and residual energies of the candidate nodes, as well as a joint distance-weighted information utility, are utilised to select the optimal group of nodes.

This allows constant identification of the $L_t = (x, y)$ objective at any time with minimal and balanced energy expenditure.




Fig 2: flow of the proposed work

Because it can handle tough nonlinear or non-Gaussian problems, the particle filter (PF) has become a useful tool in target tracking study. Monte Carlo simulation and Bayesian sampling estimation theory help support the parallel structure of PF. It is also a flexible, simple, and uncomplicated sequential significance sampling method.

Here, the PF technique is described in detail. Assuming $p(X(0))$ represents the probability distribution over initial target locations, the particle set appears as follows: $X_i(0)$, $i = 1, \dots, N_s$ $p(X(0))$.

Two times more. The formula below determines the value assigned to the $k+1$ st time instant:
 $w_{i,k+1} = w_{i,k} p(Z_{k+1} | X_{i,k+1})$ Z_{k+1} is the measured target position at $t+1$, so $p(X_{i,k+1} | X_{i,k}) q(X_{i,k} | X_{i,k}, Z_{k+1}) = w_{i,k} p(Z_{k+1} | X_{i,k+1})$. In conclusion, there is resampling. When the variance in significance weights becomes excessively large, the particle must be resampled. The formula for calculating the effective sample size is $N_{eff} = N_s / (1 + \text{Var}(w_i(k)))$.

Performance Evaluation

To test the method, we made an EANS network with 100 sensor nodes randomly put across a 100 m by 100 m area. We compare our simulated system's mean square errors, execution time, and energy cost against closest node selection, weighted distance, and entropy-based methods.




Fig 3: Number of active sensors in sensing area




Fig 4: Mean square positioning errors in different methods

Tab 2: Comparison of different approaches for tracking.

Terms		
Approaches	System Eng- cost	Fail Tracking %
Weighted distance	0.226	0.73
Closest	0.251	1.26
Entropy-based	0.243	0.63
EANS	0.213	0.66

Conclusions

Using efficient and adaptive node selection (EANS), this research improves WSN-based target monitoring. EANS utilizes a particulate discharge filter and distance-based node selection to predict desired states. Using a combined distance-weighted evaluation, the spatially-correlated node selection method establishes the importance of node information. By using spatial relationships between sensing nodes in node selection, EANS beats peers. a number of simulations, EANS is superior to beforehand methodologies in terms of energy consumption, computational complexity, and tracking precision.

References

- [1] W. Zhao, Y. Han, H. Wu, and L. Zhang, "Weighted distance based sensor selection for target tracking in wireless sensor networks," *IEEE Signal Processing Letters*, vol. 16, no. 8, pp. 647–650, 2009.
- [2] J. Qian, X. Jin, and Z. Yu, "Energy-efficient node selection for acoustic source localization in wireless sensor network," in *Proceedings of the 6th International Conference on Wireless Communications, Networking and Mobile Computing (WiCOM '10)*, pp. 1–4, Chengdu, China, September 2010.
- [3] M. Naderan, M. Dehghan, and H. Pedram, "Sensing task assignment via sensor selection for maximum target coverage in WSNs," *Journal of Network and Computer Applications*, vol. 36, no. 1, pp. 262–273, 2013.
- [4] M. Zoghi and M. H. Kahaei, "Adaptive sensor selection in wireless sensor networks for target tracking," *IET Signal Processing*, vol. 4, no. 5, pp. 530–536, 2010.
- [5] F. R. Armaghani, I. Gondal, and J. Kamruzzaman, "Dynamic sensor selection for target tracking in wireless sensor networks," in *Proceedings of the IEEE 74th Vehicular Technology Conference (VTC Fall '11)*, pp. 1–6, San Francisco, Calif, USA, September 2011.
- [6] E. Masazade, R. Niu, and P. K. Varshney, "An approximate dynamic programming based non-myopic sensor selection method for target tracking," in *Proceedings of the 46th Annual Conference on Information Sciences and Systems (CISS '12)*, pp. 1–6, March 2012.
- [7] Y. Wang and D. Wang, "Energy-efficient node selection for target tracking in wireless sensor networks," *International Journal of Distributed Sensor Networks*, vol. 2013, Article ID 830950, 6 pages, 2013.
- [8] X. Jiang, W. He, X. Yang, and Y. Wang, "An energy-efficient node selection algorithm in bearings-only target tracking sensor networks," *International Journal of Distributed Sensor Networks*, vol. 2014, Article ID 483279, 12 pages, 2014.
- [9] N. U. Hasan, W. Ejaz, S. Lee, and H. S. Kim, "Knapsack-based energy-efficient node selection scheme for cooperative spectrum sensing in cognitive radio sensor networks," *IET Communications*, vol. 6, no. 17, pp. 2998–3005, 2012.
- [10] M. Abramowitz and I. A. Stegun, *Handbook of Mathematical Functions*, Dover, New York, NY, USA, 1965.